


 Gewinde R_xR_p-EN 10226 (alt DIN 2999)

d ₁ -d ₂	SW	kg	d ₁ -d ₂	SW	kg
1/4" - 1/8"	17,0 mm	0,01	1 1/2" - 3/4"	52,0 mm	0,22
3/8" - 1/8"	20,0 mm	0,02	1 1/2" - 1"	52,0 mm	0,14
3/8" - 1/4"	20,0 mm	0,02	2" - 1"	62,5 mm	0,35
1/2" - 1/4"	25,5 mm	0,04	2" - 1 1/4"	62,5 mm	0,36
1/2" - 3/8"	25,5 mm	0,03	2" - 1 1/2"	62,5 mm	0,25
3/4" - 1/4"	32,0 mm	0,07	2 1/2" - 1 1/4"	79,5 mm	0,67
3/4" - 3/8"	32,0 mm	0,07	2 1/2" - 1 1/2"	79,5 mm	0,53
3/4" - 1/2"	32,0 mm	0,06	2 1/2" - 2"	79,5 mm	0,38
1" - 3/8"	38,0 mm	0,10	3" - 1 1/2"	93,0 mm	0,91
1" - 1/2"	38,0 mm	0,10	3" - 2"	93,0 mm	0,77
1" - 3/4"	38,0 mm	0,10	3" - 2 1/2"	93,0 mm	0,65
1 1/4" - 1/2"	46,5 mm	0,16			
1 1/4" - 3/4"	46,5 mm	0,15			
1 1/4" - 1"	46,5 mm	0,12			

