



Gewinde Rp-EN 10226 (alt DIN 2999)

d2-d1	L	kg	d2-d1	L	kg
1/4" - 1/8"	27 mm	0,03	1 1/4" - 1"	44 mm	0,17
3/8" - 1/8"	30 mm	0,04	1 1/2" - 1/2"	48 mm	0,20
3/8" - 1/4"	30 mm	0,04	1 1/2" - 3/4"	48 mm	0,17
1/2" - 1/8"	36 mm	0,07	1 1/2" - 1"	48 mm	0,34
1/2" - 1/4"	36 mm	0,07	1 1/2" - 1"	48 mm	0,34
1/2" - 3/8"	36 mm	0,07	2" - 3/4"	56 mm	0,31
3/4" - 1/4"	35 mm	0,09	2" - 1"	56 mm	0,31
3/4" - 3/8"	35 mm	0,10	2" - 1 1/4"	56 mm	0,35
3/4" - 1/2"	35 mm	0,07	2" - 1 1/2"	56 mm	0,36
1" - 3/8"	40 mm	0,16	2 1/2" - 1 1/2"	62 mm	0,76
1" - 1/2"	40 mm	0,10	2 1/2" - 2"	62 mm	0,52
1" - 3/4"	40 mm	0,11	3" - 2"	67 mm	0,73
1 1/4" - 1/2"	44 mm	0,20	3" - 2 1/2"	76 mm	0,85

