



Gewinde RxR-EN 10226 (alt DIN 2999)

d2-d1	SW	L	kg	d2-d1	SW	L	kg
1/4"- 1/8"	17,0	29	0,02	1 1/4"- 1"	46,5	46	0,16
3/8"- 1/8"	20,0	30	0,03	1 1/2"- 1/2"	52,0	51	0,20
3/8"- 1/4"	20,0	33	0,03	1 1/2"- 3/4"	52,0	49	0,34
1/2"- 1/8"	25,0	33	0,05	1 1/2"- 1"	52,0	50	0,23
1/2"- 1/4"	25,0	36	0,05	1 1/2"- 1 1/4"	52,0	50	0,23
1/2"- 3/8"	25,0	37	0,05	2"- 1"	63,0	53	0,32
3/4"- 1/4"	32,0	38	0,07	2"- 1 1/4"	63,0	56	0,34
3/4"- 3/8"	32,0	39	0,07	2"- 1 1/2"	63,0	57	0,34
3/4"- 1/2"	32,0	44	0,08	2 1/2"- 1 1/4"	80,0	69	0,60
1"- 3/8"	38,0	42	0,11	2 1/2"- 1 1/2"	80,0	69	0,78
1"- 1/2"	38,0	45	0,12	2 1/2"- 2"	80,0	64	0,56
1"- 3/4"	38,0	46	0,12	3"- 1 1/2"	98,0	71	1,00
1 1/4"- 1/2"	46,5	45	0,20	3"- 2"	93,0	66	0,78
1 1/4"- 3/4"	46,5	45	0,16	3"- 2 1/2"	92,0	68	0,95

