



**312IS Verschraubung konisch dichtend, Innengewinde/Schweißende
Union conical seat, female/butt weld end, V4A/316**

Dimension	L	SW
1/8"	24,0	25,0
1/4"	31,0	26,5
3/8"	32,0	31,0
1/2"	37,0	37,5
3/4"	42,9	46,0
1"	47,0	51,0
1 1/4"	51,0	63,0
1 1/2"	55,5	71,0
2"	63,0	83,5
2 1/2"	69,2	104,8
3"	81,9	116,8
4"	88,5	142,0

Toleranz +/- 1,0 mm



Gewinde Rp-EN 10226 (alt DIN 2999)

NW	d1	d2	L	SW	kg
8	13,5 mm	1/4"	38 mm	34 mm	0,13
10	17,2 mm	3/8"	38 mm	34 mm	0,15
15	21,3 mm	1/2"	44 mm	38 mm	0,21
20	26,9 mm	3/4"	46 mm	42 mm	0,29
25	33,7 mm	1"	48 mm	49 mm	0,42
32	42,4 mm	1 1/4"	53 mm	60 mm	0,68
40	48,3 mm	1 1/2"	63 mm	70 mm	0,82
50	60,3 mm	2"	69 mm	77 mm	1,60
65	76,1 mm	2 1/2"	87 mm	110 mm	1,80
80	88,9 mm	3"	89 mm	125 mm	2,60

