



335 Reduziermuffe, I/I Gewinde
Reducing Socket, F/F V4A/AISI 316

Dimension	L	L2	D	D2
1/4" x 1/8"	25,50	17,0	18,5	15,50
3/8" x 1/8"	29,00	17,0	21,0	15,50
3/8" x 1/4"	29,00	17,0	21,0	18,50
1/2" x 1/4"	31,00	20,0	26,0	18,50
1/2" x 3/8"	31,00	20,0	26,0	21,00
3/4" x 1/4"	30,00	22,0	32,0	18,00
3/4" x 3/8"	20,00	33,5	31,5	20,90
3/4" x 1/2"	33,50	20,0	31,5	26,00
1" x 1/4"	42,30	26,5	39,0	17,50
1" x 1/2"	38,00	24,0	39,0	26,00
1" x 3/4"	38,00	24,0	39,0	31,50
1 1/4" x 1/2"	43,20	29,0	49,5	27,60
1 1/4" x 3/4"	44,10	29,0	49,5	32,60
1 1/4" x 1"	44,00	26,0	48,5	39,00
1 1/2" x 1/2"	43,00	30,0	54,0	26,00
1 1/2" x 3/4"	46,00	31,0	56,5	32,80
1 1/2" x 1"	40,00	23,2	54,0	38,00
1 1/2" x 1 1/4"	48,50	29,5	55,0	48,50
2" x 1"	45,00	29,7	67,0	35,00
2" x 1 1/4"	49,00	30,7	67,0	49,70
2" x 1 1/2"	50,00	30,9	68,5	56,20
2 1/2" x 2"	51,50	35,7	83,5	67,00
3" x 2"	70,80	39,6	98,0	70,00
3" x 2 1/2"	71,60	38,0	98,1	84,50
4" x 3"	65,00	65,0	123	97,00

Toleranz +/- 1,0 mm